

Description

Hinged Door units (inswing). Fully Finished in White with Remmers primer ZW-400 and finish top coat DW-690.

Frame & Panels Materials

Engineered Baltic Pine (knot free). Hardwood sill.
Frame 68mm.

Preservation

All timber components are pressure impregnated with Remmers Induline GL-350 to prevent against insect and fungal attack.

Factory Finish

Doors are supplied fully finished in White as standard RAL 9010, with options for any RAL colour.
Also options for dual colour frames, or painted exterior varnish interior.

Performance

The Glazing has been tested to EN1279.

Handles and Locks

Supplied Polished Chrome as standard, options of White Anodised Silver, Polished Gold, Anodized Gold and Black.
Custom RAL colours upon request.



Weatherseal

Schlegel weather strips.

Glazing

Doors are factory glazed with Pilkington Toughened Low E glazing with upgraded Thermix Spacer and 90% Argon Gas fill, 18mm (4-10-4) tested to EN1279 U Value 1.5.

Sills

Hardwood sills.

Mechanisms

Winlock hinges, multipoint locking mechanism and furniture.

Sizing

Max height 2400mm
Min height 1800mm
Max width 1 panel 1100mm
Min width 1 panel 800mm
Max width 2 panel 2200mm
Min width 2 panel 1200mm

Grilles

FDL, 19mm profile.

Guarantees

10 years on sealed units and hardware, 5 years on paint finish against fading, 10 years on timber portions.

Black Millwork Co Inc
Andersen House
Dallow Street
Burton on Trent
Staffordshire
DE14 2PQ

Phone: 01283 511122

Fax: 01283 510863

E-mail: info@blackmillwork.co.uk

Web: www.blackmillwork.co.uk

Black
MILLWORK CO., INC.